

TOUCH PANEL DOOR BELL SYSTEM



SK-DB2000T0



SK-DB2000T1

- Touch Panel doorbell system SK-DB 2000sys. Includes three parts: SK-DB2000T0 , SK-DB 2000T1 TI Touch panel and starlight DC bell controlling unit.
- Having super deluxe external appearance, being made of ABS fire retardant and insulation material and all-metal material, and having variety of colors to match the decoration of different places such as home, office building, star level hotels.
- Blue luminescence touch screen design to pursuer modern fashion and facilitate night discrimination.
- Touch type back light instruction key design, doorbell key, clear (don't disturb) message to manifest sense of technology.
- SK-DB2000T0,SK-DB2000T1 Touch panel is suitable for standard 86 base box installations.

TECHNICAL PARAMETERS

Item	Parameter
MCU Processor	24 MHz/64K MCU
Key	1-6 port touch panel key for customized
Current Loading	One circuit for doorbell control output, one circuit special for deaf person doorbell light indication output DC60/50 HZ. 110/240V
Power of self-consumption	< 1.2 W
Connection wire	Connecting controlling terminal through 10 pin connecting terminal.
Operating Life	< 100,000 times if contactor is used under 220V And full load; 100,000 time for touch screen keys.
Operating Temperature	- 10°C – 60°C.
Operating Humidity Environment	10 – 95% under 50°C Transportation storage temperature range 20°C-80°C
Installation	Directly installed on standard 86 base box. Providing screws and holder.
External dimension	W 86mm x H 86mm x D42mm

